



MOHM CHEMICAL SDN. BHD. (Co.No.276851-U)
MCX MARKETING SDN. BHD. (Co.No.363532-T)

H. Q. : No.32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor, Malaysia.
Tel : (60 7) 333 1222 Fax : (60 7) 332 0545 / 333 7919
Branch : No. 43, Jalan Tambur 33/19, Sek. 33, Shah Alam Technology Park,
47100 Shah Alam, Selangor, Malaysia.
Tel: (60 3) 5124 0876 / 5124 0878 Fax: (60 3) 5124 0877
Email: info@mochem.com Website: www.mochem.com / www.xtraseal.com

MATERIAL SAFETY DATA SHEET

xtraseal® LIQUID GASKET

1. Product & Company Identification

1.1 Product Detail

Product name: Liquid Gasket
Physical form: Viscous Liquid
Odour: Aromatic Odour
Colour: Gray

1.2 Company Details:

Manufacturer: Mohm Chemical Sdn Bhd
Address: No. 32 (Lot 1617), Jalan Temenggong, Off Jalan Tampoi, 81100
Johor Bahru, Johor, Malaysia.
Tel: + 60-7-3331222
Fax: + 60-7-3320545/ + 60-7-3337919

2. Composition/ Hazardous Components

<u>Chemical Name</u>	<u>Approx WT%</u>
Chloroprene Rubber	<18%
Synthetic Resin	<29%
Hydrocarbon Solvent	>53%

3. Hazards Identification

Ingestion: Irritation of the mouth, throat and stomach.
Skin contact: Uncured product contact will irritate lips, gums and tongue.
Uncured product contact may irritate the skin.
Inhalation: Harmful by inhalation.
Eye contact: Uncured product contact irritates eyes.

4. First-aid Measures

In case of inhalation: Remove to fresh air, keep warm and at rest.
In case of ingestion: Seek medical advice immediately. Do not induce vomiting.
In case of skin contact: Remove contaminated clothing. Immediately clean with water and soap.
In case of eyes contact: Immediately flush with water, seek medical advice if necessary.

5. Fire Fighting Measures

Suitable extinguishing media: Use dry chemical powder, foam, carbon dioxide, water fog, sand or earth.
Unsuitable extinguishing media: Do not use Water in A Jet.



MOHM CHEMICAL SDN. BHD. (Co.No.276851-U)
MCX MARKETING SDN. BHD. (Co.No.363532-T)

H. Q. : No.32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor. Malaysia.
Tel : (60 7) 333 1222 Fax : (60 7) 332 0545 / 333 7919
Branch : No. 43, Jalan Tambur 33/19, Sek. 33, Shah Alam Technology Park,
47100 Shah Alam, Selangor. Malaysia.
Tel: (60 3) 5124 0876 / 5124 0878 Fax: (60 3) 5124 0877
Email: info@mochem.com Website: www.mochem.com / www.xtraseal.com

MATERIAL SAFETY DATA SHEET

xtraseal® LIQUID GASKET

6. Accidental release measures

Exclude sources of ignition and ventilate the area.
Exclude non-essential personnel. Avoid breathing vapours.
Collect spillages mechanically and store in suitable covered container.

7. Handling and Storage

Handling:	Ensure good ventilating during processing.
Protection against fire/ explosion:	General rules of fire prevention should be observed.
Storage:	Keep container tightly closed and dry, store in a well-ventilated area.

8. Exposure control/ Personal protection

Industrial hygiene:	Remove immediately all contaminated clothing. Do not inhale vapours.
General ventilation:	Recommended
Hand protection:	Suitable protective gloves.
Eye protection:	Safety/ protective glasses.

9. Physical and Chemical Properties

Form:	Viscous liquid
Colour:	Gray
Viscosity (30°C):	Viscosity 9000-12000cps.
Odour:	Aromatic Odour
Solid Content:	45-47%
Tack Time (Cardboard):	24 hrs
Boiling point (hPa):	110°C.
Flash point:	-32°C
Freezing point:	-16°C
Ignition temperature:	Not Determined
Density (25°C):	Density 1.180 - 1.190g/cm ³
Solubility in water (25°C)	Insoluble

Note: the above information is not intended for use in preparing specification.

10. Stability and Reactivity

Hazardous decomposition products:	None.
Hazardous reactions:	No dangerous reaction known.



MOHM CHEMICAL SDN. BHD. (Co.No.276851-U)

MCX MARKETING SDN. BHD. (Co.No.363532-T)

H.Q. : No.32,Jalan Temenggong, Off Jalan Tampoi,81100 Johor Bahru, Johor. Malaysia.

Tel : (60 7) 333 1222 Fax : (60 7) 332 0545 / 333 7919

Branch : No.43,Jalan Tambur 33/19,Sek.33,Shah Alam Technology Park,
47100 Shah Alam, Selangor. Malaysia.

Tel: (60 3) 5124 0876 / 5124 0878 Fax: (60 3) 5124 0877

Email: info@mochem.com Website: www.mochem.com / www.xtraseal.com

MATERIAL SAFETY DATA SHEET

xtraseal® LIQUID GASKET

11. Toxicological Information

On the skin:	may cause sensitisation
On the eye:	possibly irritating

12. Ecological Information

Large quantities of product should not be allowed to enter drains or water courses or be deposited where it can affect ground or surface water.

13. Disposal Considerations

Do not allow large quantities to enter the drains or water courses or dispose of where ground or surface waters may be affected. Residues in emptied containers should be covered and should be disposed of in accordance with regulations made under the control of Pollution & Environmental Protection Acts.

14. Transport Information

No dangerous goods under the transport regulations.

15. Regulatory Information

The product is classified and labeled for supply in accordance with the Classification of Hazardous Chemical. Regulations as follow.

Classification Highly Flammable
 Harmful
 Irritant to skin

Risk Phrases:	R43	May causes sensitization by skin contact. Irritant to skin
	R36/38	

Safety Phrases:	Z	Keep out of reach of children.
	S28	
	S26	After contact with skin, wash immediately with plenty of water.
	S27	
	S37	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
	S46	
		Take off immediately all contaminated clothing
		Wear suitable gloves.
		If swallowed, seek medical advice immediatly and show this container or label.



MOHM CHEMICAL SDN. BHD. (Co.No.276851-U)
MCX MARKETING SDN. BHD. (Co.No.363532-T)

H.Q. : No.32, Jalan Temenggong, Off Jalan Tampoi, 81100 Johor Bahru, Johor. Malaysia.
Tel : (60 7) 333 1222 Fax: (60 7) 332 0545 / 333 7919
Branch : No. 43, Jalan Tambur 33/19, Sek. 33, Shah Alam Technology Park,
47100 Shah Alam, Selangor. Malaysia.
Tel: (60 3) 5124 0876 / 5124 0878 Fax: (60 3) 5124 0877
Email: info@mochem.com Website: www.mochem.com / www.xtraseal.com

MATERIAL SAFETY DATA SHEET

xtraseal® LIQUID GASKET

16. Other Information

These data are offered in good faith as typical values and not as a product specification. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific content of the intended use and determine whether they are appropriate.

*** End Of MSDS ***

